



---

**MATERIAL SAFETY DATA SHEET**

---

Product Name: **"MeltDown 20 with Shield PTG Corrosion Inhibitor"**

**Corrosion inhibited granular de-icer.**

Manufacturers: Envirotech Services, Inc.                      Address: 1140 38<sup>th</sup> Ave., Greeley, CO 80634  
Redmond Minerals, Inc.    P.O. Box 219, Redmond, UT 84652

Telephone #: (970) 346-3900    Transportation Emergency: 800-535-5053  
Date Prepared: September 1, 2004                                      Date Updated: December 15, 2007

---

**SECTION I: Hazardous Ingredients**

---

None

---

**SECTION II: Physical/Chemical Characteristics**

---

Boiling Point:	N/D	Solubility in Water:	96%
Vapor Pressure:	N/D	Vapor Density:	ND
Evaporation Rate:	N/D	Freezing Point:	N/D
Solubility in Water:	Soluble	Melting Point:	N/D
Appearance and Odor:	Red to brown granular material, mild odor		

---

**SECTION III: Reactivity Data**

---

STABILITY: Stable  
INCOMPATIBILITY: Leather  
HAZARDOUS DECOMPOSITION PRODUCTS: None known.  
HAZARDOUS POLYMERIZATION: Will not occur

---

**SECTION IV: Health Hazard Data**

---

**POTENTIAL EFFECTS OF EXPOSURE:**

EYES: Mild irritant may occur.  
SKIN: Prolonged contact without normal hygiene may cause irritation and skin dryness.  
INHALATION: Inhalation may cause irritation to nose, lungs, and chest.  
INGESTION: Ingestion may cause nausea in large quantities.

**FIRST AID:**

EYES: Flush with water. Use over the counter eye drops if necessary and compatible with worker.  
SKIN: Normal hygiene, wash with mild soap and water, rinse.  
INHALATION: Remove to fresh air  
INGESTION: Give lukewarm water (1 pint) – induce vomiting.

