

1. Identification of the substance/mixture and of the company/undertaking

Product name	2K Urethane Primer (Gray)	
Product code	421-19™	141216
Intended use	Coating for professional use	
	Axalta Coating Systems, LLC Applied Corporate Center 50 Applied Card Way, Suite 300 US Glen Mills, PA 19342	
Telephone	Product information	(855) 6-AXALTA
	Medical emergency	(855) 274-5698
	Transportation emergency	(800) 424-9300 (CHEMTREC)

2. Hazards identification

This preparation is hazardous per the following GHS criteria

GHS-Classification

Flammable liquids	Category 2
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Toxicity for reproduction	Category 2

Endpoints which are “not classified”, “cannot classified” and “not applicable” are not shown

GHS-Labeling



Hazard symbols

Signal word

Danger

Hazard statements

Highly flammable liquid and vapour.
Causes skin irritation.
Causes serious eye irritation.
Suspected of damaging fertility or the unborn child.

Precautionary statements

Ground/bond container and receiving equipment.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Obtain special instructions before use.
Take precautionary measures against static discharge.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.
Wear protective gloves/protective clothing/eye protection/face protection.
IF exposed or concerned: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation occurs: Get medical advice/ attention.

SAFETY DATA SHEET

421-19™ v4.0
en/US



Specific treatment (see supplemental first aid instructions on this label).
Take off contaminated clothing and wash before reuse.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local regulations.

Other hazards which do not result in classification

None known.

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity:

0 %

3. Composition/information on ingredients

Mixture of synthetic resins, pigments, and solvents

Components

CAS-No.	Chemical Name	Concentration
1330-20-7	Xylene	12%
123-86-4	Butyl acetate	
78-93-3	Methyl ethyl ketone	
108-65-6	Propylene glycol monomethyl ether acetate	
100-41-4	Ethylbenzene	3.0%
110-12-3	Methyl isoamyl ketone	

Non-regulated ingredients 60 - 70%

OSHA Hazardous: Yes

* Assigned CAS No. - An official CAS No. does not exist. The CAS No. shown is for a similar chemical.

4. First aid measures

Eye contact

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

Skin contact

Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

Inhalation

Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

Ingestion

If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. Keep at rest.

SAFETY DATA SHEET

421-19™ v4.0
en/US



Most Important Symptoms/effects, acute and delayed

Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. If this product mixed with an isocyanate activator/hardener (see MSDS for the activator), the following health effects may apply: Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

Ingestion

May result in gastrointestinal distress.

Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis. If this product is mixed with an isocyanate, skin contact may cause sensitization.

Indication of Immediate medical attention and special treatment needed if necessary

No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

5. Firefighting measures

Suitable extinguishing media

Universal aqueous film-forming foam, Carbon dioxide (CO₂), Dry chemical

Extinguishing media which shall not be used for safety reasons

High volume water jet

Hazardous combustion products

CO, CO₂, smoke, and oxides of any heavy metals that are reported in "Composition, Information on Ingredients" section.

Fire and Explosion Hazards

Flammable liquid. Vapor/air mixture will burn when an ignition source is present.

Special Protective Equipment and Fire Fighting Procedures

Full protective flameproof clothing should be worn as appropriate. Wear self contained breathing apparatus for fire fighting if necessary. In the event of fire, cool tanks with water spray. Do not allow run-off from fire fighting to enter public sewer systems or public waterways.

6. Accidental release measures

Procedures for cleaning up spills or leaks

Ventilate area. Remove sources of ignition. Prevent skin and eye contact and breathing of vapor. If the material contains, or is mixed with an isocyanate activator/hardener: Wear a positive-pressure, supplied-air respirator (NIOSH approved TC-19C), eye protection, gloves and protective clothing. Pour liquid decontamination solution over the spill and allow to sit at least 10 minutes. Typical decontamination solutions for isocyanate containing materials are: 20% Surfactant (Tergitol TMN 10) and 80% Water OR 0 -10% Ammonia, 2-5% Detergent and Water (balance) Pressure can be generated. Do not seal waste containers for 48 hours to allow CO₂ to vent. After 48 hours, material may be sealed and disposed of properly. If material does not contain or is not mixed with an isocyanate activator/hardener: Wear a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH approved TC-23C), eye protection, gloves and protective clothing. Confine, remove with inert absorbent, and dispose of properly.

Environmental precautions

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

7. Handling and storage

Precautions for safe handling

Observe label precautions. Keep away from heat, sparks, flame, static discharge and other sources of ignition. VAPORS MAY CAUSE FLASH FIRE. Close container after each use. Ground containers when pouring. Do not transfer contents to bottles or unlabeled containers. Wash thoroughly after handling and before eating or smoking. Do not store above 49 °C (120 °F). If material is a coating: do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves. Combustible dust clouds may be created where operations produce fine material (dust). Avoid formation of significant deposits of material as they may become airborne and form combustible dust clouds. Build up of fine material should be cleaned using gentle sweeping or vacuuming in accordance with best practices. Cleaning methods (e.g. compressed air) which can generate potentially combustible dust clouds should not be used.

Advice on protection against fire and explosion

Solvent vapours are heavier than air and may spread along floors. Vapors may form explosive mixtures with air and will burn when an ignition source is present. Always keep in containers of same material as the original one. Never use pressure to empty container: container is not a pressure vessel. The accumulation of contaminated rags may result in spontaneous combustion. Good housekeeping standards and regular safe removal of waste materials will minimize the risks of spontaneous combustion and other fire hazards.

Storage

Requirements for storage areas and containers

Observe label precautions. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage

Store separately from oxidizing agents and strongly alkaline and strongly acidic materials.

OSHA/NFPA Storage Classification: IB

8. Exposure controls/personal protection

Engineering controls and work practices

Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

National occupational exposure limits

CAS-No.	Chemical Name	Source	Time	Type	Value	Note
1330-20-7	Xylene	ACGIH	15 min	STEL	150 ppm	
			8 hr	TWA	100 ppm	
		OSHA	8 hr	TWA	100 ppm	
		Dupont	8 & 12 hour	TWA	100 ppm	
123-86-4	Butyl acetate	ACGIH	15 min	STEL	200 ppm	
			8 hr	TWA	150 ppm	
		OSHA	8 hr	TWA	150 ppm	
78-93-3	Methyl ethyl ketone	ACGIH	15 min	STEL	300 ppm	
			8 hr	TWA	200 ppm	
		OSHA	8 hr	TWA	200 ppm	

SAFETY DATA SHEET421-19™ v4.0
en/US

CAS-No.	Chemical Name	Source	Time	Type	Value	Note
		Dupont	15 min	TWA	300 ppm	
			8 & 12 hour	TWA	200 ppm	
108-65-6	Propylene glycol monomethyl ether acetate	Dupont	15 min	TWA	30 ppm	
100-41-4	Ethylbenzene	ACGIH	8 hr	TWA	20 ppm	
		OSHA	8 hr	TWA	100 ppm	
		Dupont	8 & 12 hour	TWA	25 ppm	
110-12-3	Methyl isoamyl ketone	ACGIH	8 hr	TWA	20 ppm	

** STEL = Short term exposure limit.
TWA = Time-weighted average.

Protective equipment

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

Respiratory protection

Do not breathe vapors or mists. When this product is used with an isocyanate activator/hardener, wear a positive-pressure, supplied-air respirator (NIOSH approved TC-19C) while mixing activator/hardener with paint, during application and until all vapors and spray mist are exhausted. If product is used without isocyanate activator/hardener, a properly fitted air-purifying respirator with organic vapor cartridges (NIOSH TC-23C) and particulate filter (NIOSH TC-84A) may be used. Follow respirator manufacturer's directions for respirator use. Do not permit anyone without protection in the painting area. Refer to the hardener/activator label instructions and MSDS for further information. Individuals with history of lung or breathing problems or prior reaction to isocyanates should not use or be exposed to this product if mixed with isocyanate activators/hardeners.

Eye protection

Desirable in all industrial situations. Goggles are preferred to prevent eye irritation. If safety glasses are substituted, include splash guard or side shields.

Skin and body protection

Neoprene gloves and coveralls are recommended.

Hygiene measures

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Environmental exposure controls

Do not let product enter drains. For ecological information, refer to Ecological Information Section 12.

9. Physical and chemical properties

Appearance

Form: liquid Colour: grey

Flash point	44 °F
Ignition temperature	272 °C

SAFETY DATA SHEET

421-19™ v4.0

en/US



Lower Explosive Limit	1 %	
Upper Explosive Limit	12 %	
Evaporation rate	Slower than Ether	
Vapor pressure of principal solvent	11.9 hPa	
Water solubility	appreciable	
Vapor density of principal solvent (Air = 1)	3.7	
Approx. Boiling Range	78 °C	
Approx. Freezing Range	Not applicable.	
Gallon Weight (lbs/gal)	11.92	
Specific Gravity	1.43	
Percent Volatile By Volume	57.42%	
Percent Volatile By Weight	34.50%	
Percent Solids By Volume	42.58%	
Percent Solids By Weight	65.50%	
pH (waterborne systems only)	No data available.	
Partition coefficient: n-octanol/water	no data available	
Ignition temperature	272 °C	DIN 51794
Decomposition temperature		
Viscosity (23 °C)	Not applicable.	ISO 2431-1993
VOC* less exempt (lbs/gal)	4.1	
VOC* as packaged (lbs/gal)	4.0	

* VOC less exempt (theoretical) and VOC as packaged (theoretical) are based upon the VOC of the packaged material at the point of manufacture.

10. Stability and reactivity

Stability

Stable

Conditions to avoid

Stable under recommended storage conditions.

Materials to avoid

None reasonably foreseeable.

Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

Hazardous Polymerization

Will not occur.

Sensitivity to Static Discharge

Solvent vapors in air may explode if static grounding and bonding is not used during transfer of this product.

Sensitivity to Mechanical Impact

None known.

11. Toxicological information

Information on likely routes of exposure

SAFETY DATA SHEET

421-19™ v4.0
en/US



Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. If this product mixed with an isocyanate activator/hardener (see MSDS for the activator), the following health effects may apply: Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

Ingestion

May result in gastrointestinal distress.

Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

Delayed and immediate effects and also chronic effects from short and long term exposure:

Acute oral toxicity

not hazardous

Acute dermal toxicity

not hazardous

Acute inhalation toxicity

not hazardous

% of unknown composition 0 %

Skin corrosion/irritation

xylene	Category 2
n-butyl acetate	Category 3
butanone	Category 3
ethylbenzene	Category 3
5-methylhexan-2-one	Category 3

Serious eye damage/eye irritation

xylene	Category 2A
butanone	Category 2A
2-methoxy-1-methylethyl acetate	Category 2A
ethylbenzene	Category 2B
5-methylhexan-2-one	Category 2A

Respiratory sensitisation

Not classified according to GHS criteria

Skin sensitisation

Not classified according to GHS criteria

Germ cell mutagenicity

Not classified according to GHS criteria

SAFETY DATA SHEET

421-19™ v4.0
en/US



Carcinogenicity

Not classified according to GHS criteria

Toxicity for reproduction

No data available.

Target Organ Systemic Toxicant - Single exposure

Not classified according to GHS criteria

Target Organ Systemic Toxicant - Repeated exposure

Not classified according to GHS criteria

Aspiration toxicity

Not classified according to GHS criteria

Numerical measures of toxicity (acute toxicity estimation (ATE),etc.)

No information available.

Symptoms related to the physical, chemical and toxicological characteristics

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Through skin resorption, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

Whether the hazardous chemical is listed by NTP, IARC or OSHA

Titanium dioxide	IARC 2B
ethylbenzene	IARC 2B
carbon black	IARC 2B

12. Ecological information

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

13. Disposal considerations

Waste Disposal Method

Do not allow material to contaminate ground water systems. Incinerate or otherwise dispose of waste material in accordance with Federal, State, Provincial, and local requirements. Do not incinerate in closed containers.

14. Transport information

International transport regulations

IMDG (Sea transport)

UN number:	1263
Proper shipping name:	PAINT

Hazard Class:	3
Subsidiary Hazard Class:	Not applicable.
Packing group:	II
Marine Pollutant:	no

SAFETY DATA SHEET421-19™ v4.0
en/US**ICAO/IATA (Air transport)**UN number: 1263
Proper shipping name: PAINTHazard Class: 3
Subsidiary Hazard Class: Not applicable.
Packing group: II**DOT**UN number: 1263
Proper shipping name: PAINTHazard Class: 3
Subsidiary Hazard Class: Not applicable.
Packing group: II
Marine Pollutant: no
EmS: F-E,S-E**Matters needing attention for transportation**

Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

15. Regulatory information**TSCA Status**

In compliance with TSCA Inventory requirements for commercial purposes.

DSL Status

All components of the mixture are listed on the DSL.

Photochemical Reactivity

Photochemically reactive

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)

WARNING! This product contains a chemical known to the State of California to cause cancer.

Regulatory information

CAS #	Ingredient	EPCRA					CERCLA RQ(lbs)	CAA HAP
		302	TPQ	RQ	311 - 312	313		
1330-20-7	Xylene	N	NR	NR	A,C,F,N,R	Y	100	Y
123-86-4	Butyl acetate	N	NR	NR	A,C,F	N	NR	N
78-93-3	Methyl ethyl ketone	N	NR	NR	A,C,F	N	5,000	N
108-65-6	Propylene glycol monomethyl ether acetate	N	NR	NR	F	N	NR	N
100-41-4	Ethylbenzene	N	NR	NR	A,C,F	Y	1,000	Y
110-12-3	Methyl isoamyl ketone	N	NR	NR	C	N	NR	N

Key:

EPCRA	Emergency Planning and Community Right-to-know Act (aka Title III, SARA)
302	Extremely hazardous substances
311/312 Categories	F = Fire Hazard A = Acute Hazard R = Reactivity Hazard C = Chronic Hazard

SAFETY DATA SHEET

421-19™ v4.0
en/US



	P = Pressure Related Hazard
313 Information	Section 313 Supplier Notification - The chemicals listed above with a 'Y' in the 313 column are subject to reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know act of 1986 and of 40 CFR 372.
CERCLA	Comprehensive Emergency Response, Compensation and Liability Act of 1980.
HAP	Listed as a Clean Air Act Hazardous Air Pollutant.
TPQ	Threshold Planning Quantity.
RQ	Reportable Quantity
NA	not available
NR	not regulated

16. Other information

HMIS rating H: 2 F: 3 R: 0

Glossary of Terms:

ACGIH	American Conference of Governmental Industrial Hygienists.
IARC	International Agency for Research on Cancer.
NTP	National Toxicology Program.
OEL	Occupational Exposure Limit
OSHA	Occupational Safety and Health Administration.
STEL	Short term exposure limit.
TWA	Time-weighted average.
PNOR	Particles not otherwise regulated.
PNOC	Particles not otherwise classified.

NOTE: The list (above) of glossary terms may be modified.

Notice from Axalta Coating Systems

The document reflects information provided to Axalta Coating Systems by its suppliers. Information is accurate to the best of our knowledge and is subject to change as new data is received by Axalta Coating Systems. Persons receiving this information should make their own determination as to its suitability for their purposes prior to use. The information on this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

SDS prepared by:

Axalta Coating Systems Regulatory Affairs

Report version

Version	Changes
4.0	7, 9, 15, 16

Revision Date: 2015-05-05

(855) 6-AXALTA
nasonfinishes.us

axalta.us

