



Safety Data Sheet

Spartan Chemical Company, Inc.

Revision Date: 31-Jul-2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name: NEW GENERATION 100 GREY PART A
Product Number: 5862A
Recommended Use: Concrete seal
Uses Advised Against: For Industrial and Institutional Use Only

Manufacturer/Supplier: Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee, Ohio 43537 USA
800-537-8990 (Business hours)
www.spartanchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information: 888-314-6171
Transportation/Spill/Leak: CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

GHS Classification

Skin Corrosion/Irritation: Category 2
Serious Eye Damage/Eye Irritation: Category 2A
Skin Sensitization: Category 1
Carcinogenicity: Category 2

GHS Label Elements

Signal Word:

Symbols:

Warning



Hazard Statements:

Causes skin irritation.
Causes serious eye irritation
May cause an allergic skin reaction
Suspected of causing cancer

Precautionary Statements:

Prevention:

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wear eye / face protection
Wear protective gloves
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash hands and any exposed skin thoroughly after handling.
Contaminated work clothing should not be allowed out of the workplace

Response:

-Eyes

If exposed or concerned: Get medical attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

-Skin

IF ON SKIN (or hair): Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs: Get medical attention.

-Specific Treatment:	See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.
Storage:	Store locked up.
Disposal:	Dispose of contents and container in accordance with local, state and federal regulations.
Hazards Not Otherwise Classified:	Not Applicable
Other Information:	<ul style="list-style-type: none"> • May be harmful if swallowed. • Keep out of reach of children.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
epoxy resin	25068-38-6	40-70
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	10-30
titanium dioxide	13463-67-7	1-5
polyester resin	PROPRIETARY	1-5
C.I. pigment black 7	1333-86-4	0.1-1

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

-Eye Contact:	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
-Skin Contact:	Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs: Get medical attention.
-Inhalation:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison control center or physician if you feel unwell.
-Ingestion:	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention if you feel unwell.
Note to Physicians:	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:	Product does not support combustion, Use extinguishing agent suitable for type of surrounding fire
Specific Hazards Arising from the Chemical:	Dried product is capable of burning. Combustion products are toxic.
Hazardous Combustion Products:	May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.
Protective Equipment and Precautions for Firefighters:	Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Cool fire-exposed containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.
Environmental Precautions:	Do not rinse spill onto the ground, into storm sewers or bodies of water.
Methods for Clean-Up:	Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Advice on Safe Handling:	Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.
---------------------------------	--

Storage Conditions: Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Keep from freezing.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³
C.I. pigment black 7 1333-86-4	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

Engineering Controls: Provide good general ventilation.
If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other engineering controls should be considered.

Personal Protective Equipment

Eye/Face Protection: Wear splash goggles.

Skin and Body Protection: Wear rubber or other chemical-resistant gloves.

Respiratory Protection: Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section 3 should be considered.

General Hygiene Considerations: Wash hands and any exposed skin thoroughly after handling.
See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Liquid
Color:	Grey
Odor:	Odorless
pH:	Not applicable
Melting Point / Freezing Point:	No information available.
Boiling Point / Boiling Range:	> 204 °C / 399 °F
Flash Point:	> 100 °C / > 212 °F Estimated
Evaporation Rate:	< 1 (Butyl acetate = 1)
Flammability (solid, gas)	No information available.
Upper Flammability Limit:	No information available.
Lower Flammability Limit:	No information available.
Vapor Pressure:	No information available.
Vapor Density:	No information available.
Specific Gravity:	1.14
Solubility(ies):	Insoluble in water
Partition Coefficient:	No information available.
Autoignition Temperature:	No information available.
Decomposition Temperature:	No information available.
Viscosity:	No information available.

10. STABILITY AND REACTIVITY

Reactivity: This material is considered to be non-reactive under normal conditions of use.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Not expected to occur with normal handling and storage.

Conditions to Avoid: Extremes of temperature and direct sunlight.

Incompatible Materials: Strong oxidizing agents. Strong acids.

Hazardous Decomposition Products: May include carbon monoxide, carbon dioxide (CO₂) and other toxic gases or vapors.

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Eyes, Skin, Ingestion, Inhalation.
Symptoms of Exposure:
-Eye Contact: Pain, redness, swelling of the conjunctiva and blurred vision.
-Skin Contact: Pain, redness and cracking of the skin. May cause sensitization by skin contact
-Inhalation: Nasal discomfort and coughing.
-Ingestion: Pain, nausea, vomiting and diarrhea.
Immediate, Delayed, Chronic Effects
Product Information: Data not available or insufficient for classification.

Target Organ Effects: Lungs. Respiratory System.

Numerical Measures of Toxicity

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral): 12970 mg/kg

Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
epoxy resin 25068-38-6	= 11400 mg/kg (Rat)	Not Available	Not Available
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	= 17100 mg/kg (Rat)	Not Available	Not Available
titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	Not Available	Not Available
C.I. pigment black 7 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	Not Available

Carcinogenicity: The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
titanium dioxide 13463-67-7	Not Listed	Group 2B	Not Listed	Listed
C.I. pigment black 7 1333-86-4	Not Listed	Group 2B	Not Listed	Listed

IARC (International Agency for Research on Cancer): Group 2B - Possibly Carcinogenic to Humans

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
C.I. pigment black 7 1333-86-4	Not Available	Not Available	Not Available	5600: 24 h Daphnia magna mg/L EC50

Persistence and Degradability: No information available.

Bioaccumulation: No information available.

Other Adverse Effects: No information available.

13. DISPOSAL CONSIDERATIONS

Disposal of Wastes: Dispose of in accordance with federal, state and local regulations.

Contaminated Packaging: Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT:	Not Regulated
Proper Shipping Name:	Non Hazardous Product
Special Provisions:	Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation expert for information specific to your situation.
IMDG:	Not Regulated
Proper Shipping Name:	Non Hazardous Product

15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313

This product does not contain listed substances above the "de minimus" level

SARA 311/312 Hazard Categories

Acute Health Hazard:	Yes
Chronic Health Hazard:	Yes
Fire Hazard:	No
Sudden release of pressure hazard:	No
Reactive Hazard:	No

California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

16. OTHER INFORMATION

NFPA	Health Hazards: 2	Flammability: 0	Instability: 0	Special: N/A
HMIS	Health Hazards: 2*	Flammability: 0	Physical Hazards: 0	

Revision Date:	31-Jul-2015
Reasons for Revision:	Section 14 and 15

Disclaimer:

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet